

NeoVision24 TopFlex

Flexible Neon LED Tape Specification Sheet

GM Lighting®

PRODUCT OVERVIEW

A 24VDC high transmission, flexible linear 'neon' tape that is field cuttable and joinable. Designed for applications that require ultra-rich light and color saturation that is characteristic of neon. TopFlex enables vertical bending that conforms tape around curvilinear surfaces.

FEATURES

- Multiple power feed options
- Tape encased in UV stable silicone (UV protected)
- Wireless control with LUXcontrol App and controller
- 2700K, 3000K, 4000K / Amber, Blue, Green or Red
- 120° viewing angle
- Maximum run: 32'-8"
- Cuttable and joinable in two inch increments
- Each run requires an end cap (sold separately)
- No tools required for capping and joining
- Mounting clips included (recommend use one per foot)

SPECIFICATIONS

ELECTRICAL

- 24VDC
- 3W per foot

PHOTOMETRIC

- 90+ CRI

AMBIENT OPERATING TEMP

- -13°F - 131°F

CERTIFICATION

- UL
- IP65

WARRANTY

- 5 years when paired with GM power supply

ORDERING INFORMATION

White

Product No.	Length	Lumens/ft	Color Temp
NV24T-3W-27K-16	16'-4"	215lm	2700K
NV24T-3W-27K-32	32'-8"	215lm	2700K
NV24T-3W-30K-16	16'-4"	230lm	3000K
NV24T-3W-30K-32	32'-8"	230lm	3000K
NV24T-3W-40K-16	16'-4"	215lm	4000K
NV24T-3W-40K-32	32'-8"	215lm	4000K

Colors

Product No.	Length	Lumens/ft	Color Temp
NV24T-3W-AM-16	16'-4"	N/A	Amber
NV24T-3W-AM-32	32'-8"	N/A	Amber
NV24T-3W-BL-16	16'-4"	N/A	Blue
NV24T-3W-BL-32	32'-8"	N/A	Blue
NV24T-3W-GR-16	16'-4"	N/A	Green
NV24T-3W-GR-32	32'-8"	N/A	Green
NV24T-3W-RD-16	16'-4"	N/A	Red
NV24T-3W-RD-32	32'-8"	N/A	Red

Max Run: 32'-8"

Kelvin temperature (color) ±100K.


NOTE: Every reel includes (1) **NV24T-PF-EF** (tape-to-power feed with 48" of lead). 16' reel includes (16) **NV24T-MC-A** mounting clips and screws. 32' reel comes with (32) **NV24T-MC-A** mounting clips and screws.

GM Lighting®

©2025 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice
18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net

NV24T-3W_02.11.2025
Page 1

Project Name	Type
Catalog #	Date



NeoVision24 TopFlex

Flexible Neon LED Tape Specification Sheet




CONNECTORS AND ACCESSORIES


Product No.	Description
NV24T-PF-EF8	Tape-to-Power Flexible End Feed, 8 ft.
NV24T-PF-BF8	Tape-to-Power Flexible Bottom Feed, 8 ft.
NV24T-SP	Tape-to-Tape Splice Connector
NV24T-CHL-A4	Aluminum Channel, 4 ft.
NV24T-CHL-A6	Aluminum Channel, 6 ft.
NV24T-MC-A	Aluminum Mounting Clips (set of 20)

Product No.	Description
NV24T-TTC6	Tape-to-Tape Flexible Connector, 6"
NV24T-TTC12	Tape-to-Tape Flexible Connector, 12"
NV24T-TTC24	Tape-to-Tape Flexible Connector, 24"
NV24T-FLEX-CHL	Flexible Mounting Channel, 39.5"
NV24T-EC	End Cap
NV24-CT	Tape Cutting Tool

The above connectors, channels, mounting clips and caps are for the exclusive use of **NeoVision24 TopFlex Neon Tape** and are ordered separately.



Tape Configuration Example




NeoVision24 TopFlex

Flexible Neon LED Tape Specification Sheet


GM Lighting®

DIMENSIONS


NV24T-PF-EF8




NV24T-PF-BF8




NV24T-SP




NV24T-EC




NV24T-CHL-A4 (4' L)
NV24T-CHL-A6 (6' L)




NV24T-MC-A




NV24T-FLEX-CHL



NV24S-TTC6 | NV24S-TTC12 | NV24S-TTC24



TopFlex Tape




NeoVision24 TopFlex

Flexible Neon LED Tape Specification Sheet



GMLighting®

WIRING DIAGRAM

Single Color Smart Controller



Repeater Wiring Single color connection - One channel



CONTROLLERS

Product No.	Description
SHWC*	Smart 2.4 GHz WiFi Controller, Standard 12V/24V Low Voltage, 1-Channel / 2-Wire
SHWC-RGBW-RPT*	Universal Smart Power Repeater

*NOTE: For use with LD-E (non-dimmable) or LD-XD (dimmable) power supply only.
Not compatible with LD-MD (magnetic) power supply.




POWER SUPPLIES

Product No.	Description
LD-XD Series	LineDRIVE 24V Dimmable Power Supplies
LD-MD Series	LineDRIVE 24V Magnetic Power Supplies
PSD Series	Constant Voltage 24V Dimmable Power Supplies

NeoVision24 TopFlex

Flexible Neon LED Tape Specification Sheet


SHWC LUXCONTROL WIFI CONTROLLER



NeoVision24 TopFlex

Flexible Neon LED Tape Specification Sheet


SHWC LUXCONTROL WIFI CONTROLLER WITH POWER REPEATER



NeoVision24 TopFlex


Flexible Neon LED Tape Specification Sheet

SHWD LUXCONTROL WIFI CONTROLLER



SHWD SWD DRIVER AND DIMMER

SWITCHLD - SWD
12VDC or 24VDC
12V - 48W MAX LOAD
24V - 80W MAX LOAD




NeoVision24 TopFlex

Flexible Neon LED Tape Specification Sheet

GM Lighting®

RF CONTROLLER



CONTROLLERS

Product No.	Description
HC-RF-UNV-5CH	Universal 1-5 Channel RF Remote Control
CM-RF-UNV-5CH	Universal 1-5 Channel Control Module
RPT-UNV-5CH	Universal 1-5 Channel Repeater Amplifier

Note: Multiple power supplies can be replaced with a single multi-output power supply.

POWER SUPPLIES

Product No.	Description
LD-E-UNV Series	LineDRIVE 12V / 24V Non-Dimmable Power Supplies
LD-XD-UNV Series	LineDRIVE 12V / 24V Power Supplies
LTP Series	24V Electronic LED Power Supplies


NeoVision24 TopFlex

Flexible Neon LED Tape Specification Sheet


GMLighting®

RF REMOTE CONTROLLER AND REPEATER

Use 12V or 24V dc to match LED voltage



DIMENSIONS



NeoVision24 TopFlex

Flexible Neon LED Tape Specification Sheet

GMLighting®

RF HAND HELD REMOTE FEATURES AND DIMENSIONS

