

# Path Light

## ILS-P202-AB 2 Tier Hat Path Light Specification Sheet



### PRODUCT OVERVIEW

The Irradiar Landscape Path Lights by GM Lighting are premium-grade, pathway lights designed to enhance outdoor spaces with subtle and even illumination. Engineered for functionality and style, these path lights feature durable construction and an elegant design, making them perfect for guiding pathways, accentuating garden beds, and adding ambiance to your landscape.

### FEATURES

- 2-Tier classic hat blends with many styles
- Die-cast brass (8.4" Dia. x 24"H)
- Frosted glass / white reflector optics
- Antique Brass finish
- Ground Stake (included)
- G4 LED lamps (not included)
- 360° downlight smooth distribution
- 6ft Direct Burial Cable, 18AWG

### SPECIFICATIONS

#### ELECTRICAL

- 12V (nominal) low voltage
- 4W G4 (max lamp wattage)

#### CERTIFICATION

- cETLus
- IP65

#### WARRANTY

- 10 years (visit: [gmlighting.net/warranty](http://gmlighting.net/warranty))

|              |      |
|--------------|------|
| Project Name | Type |
| Catalog #    | Date |



### ORDERING INFORMATION:

#### 1. SELECT FIXTURE

| Product No. | Description           |
|-------------|-----------------------|
| ILS-P202-AB | 2 Tier Hat Path Light |

#### 2. SELECT A COMPATIBLE GM LAMP

**G4 (WP series, Water Protection): WHITE | G4 (Damp Location): WHITE**

| Watts | CCT   | Lumens | WP series      | Damp Location |
|-------|-------|--------|----------------|---------------|
| 2W    | 2700K | 180lm  | LG427K-02W0MWP | LG427K-02W01S |
|       | 3000K | 180lm  | LG430K-02W0MWP | LG430K-02W01S |
|       | 4000K | 180lm  | LG440K-02W0MWP | LG440K-02W01S |
| 3W    | 2700K | 270lm  | LG427K-03W0MWP | LG427K-03W01S |
|       | 3000K | 270lm  | LG430K-03W0MWP | LG430K-03W01S |
|       | 4000K | 270lm  | LG440K-03W0MWP | LG440K-03W01S |
| 4W    | 2700K | 380lm  | LG427K-04W0MWP | LG427K-04W01S |
|       | 3000K | 380lm  | LG430K-04W0MWP | LG430K-04W01S |
|       | 4000K | 380lm  | LG440K-04W0MWP | LG440K-04W01S |

NOTE: Lamps must be used in an outdoor rated luminaire for landscape applications.


# Path Light

## ILS-P202-AB 2 Tier Hat Path Light Specification Sheet



### 3. SELECT COMPATIBLE ACCESSORIES

| Product No. | Description                                                                            |
|-------------|----------------------------------------------------------------------------------------|
| ILS-A100P   | ILS LG Stake W/Slot Black<br>ABS 1/2 NPS                                               |
| ILS-A110P   | ILS SM Stake W/Slot Black<br>ABS 1/2 NPS                                               |
| ILS-A130-AB | ILS Stake Cover Brass<br>Antique Brass Finish                                          |
| ILS-A540-AB | ILS Round Surface Mount Brass,<br>Antique Brass Finish<br>Set Screw 3X SS Black Screws |
| ILS-A541-AB | ILS Cone Surface Mount Brass,<br>Antique Brass Finish<br>Set Screw 3x SS Black Screws  |
| ILS-A530-AB | ILS Tri-Point Surface Mount Brass,<br>Antique Brass Finish<br>3x SS Black Screws       |
| ILS-A302-AB | ILS Direct Light Fitting Brass<br>Internal 1/2" IPS Threads<br>Antique Brass Finish    |
| ILS-A700-AB | 1/2" NPS Locknut Brass                                                                 |

|                                                                                                                               |                                                                                                                                    |
|-------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| <br>ILS LG Stake<br>ILS-A100P               | <br>ILS SM Stake<br>ILS-A110P                   |
| <br>LS SM Stake Cover<br>ILS-A130-AB        | <br>ILS RND Surface Mount<br>ILS-A540-AB        |
| <br>ILS Cone Surface Mount<br>ILS-A541-AB  | <br>ILS Tri-Point Surface Mount<br>ILS-A530-AB |
| <br>1/2" NPS Locknut Brass<br>ILS-A700-AB | <br>ILS Fitting<br>ILS-A302-AB                |

### 4. SELECT COMPATIBLE POWER SUPPLY

Fixtures must be used with 12V nominal power supply. See transformers specification sheets for details, controls and related accessories.

| Product No.  | Watts         | Voltage                          |
|--------------|---------------|----------------------------------|
| ILS-S075A-SS | 75W           | 120Vin, 12/15Vout                |
| ILS-S150B-SS | 150W          | 120Vin, 12/13/14/15Vout          |
| ILS-S300B-SS | 300W          | 120Vin, 12/13/14/15/17/18/22Vout |
| ILS-S600B-SS | 600W (2X300W) | 120Vin, 12/13/14/15/17/18/22Vout |
| ILS-S100C-PC | 100W          | 120Vin, 12/15Vout                |



# Path Light

## ILS-P202-AB 2 Tier Hat Path Light Specification Sheet



### DIMENSIONS

